



机型特点 Model Features



- 多种控制模式适用于各种自动拧紧设备。
Various control modes are suitable for various automatic tightening equipment.
- 无需改装或增加配件，连接控制器直接使用。
No need to modify or expand accessories, just connect with the power controller to use directly.
- 采用协议通讯与设备连接，有效屏蔽干扰信号。
Using protocol communication to connect with devices to effectively shield interference signals.
- 全新设计的一体式电源信号控制器，使用端子接线，确保无间断连接。
The newly designed integrated power signal controller uses terminal wiring to ensure an continuous connection.

技术参数 Technical parameters

型号 Model	扭力范围 Torque Range		空载转速 No load speed(r. p. m)		输入电压 Input voltage	重量 Weight(g)	标准批头 Screw bit		
	Kgf.cm	N.m	HI	LO					
SD-CA200AT	0.1-1.5	0.01-0.15	1000	800	30V	330	Ø4mm		
SD-CA300AT	0.2-3.5	0.02-0.34							
SD-CA400AT	0.3-6.5	0.03-0.63							
SD-CA450AT	1-10	0.1-1	2000	1600		520	Ø5mm		
SD-CA450FAT									
SD-CA500AT	2-12	0.2-1.18	1000	800					
SD-CA500FAT			2000	1600					
SD-CA550AT	3-19	0.29-1.86	1000	800				640	1/4-Hex
SD-CA550FAT	3-17	0.29-1.66	2000	1600					
SD-CA600AT	5-25	0.5-2.45	1000	800					
SD-CA600FAT	5-23	0.5-2.25	2000	1600					
SD-CA620AT	10-30	0.98-2.94	1000	800					
SD-CA620FAT			2000	—					
SD-CA630AT	10-35	0.98-3.43	650	450					
SD-CA700AT	15-45	1.47-4.41	1000	—					
SD-CA730AT	20-50	1.96-4.9							

可选输出端子起子头规格
Optional output terminal screwdriver head specifications

应用 Application



电源技术参数 Technical parameters of power supply

型号 Model	输出功率 Output power	输出电压 Output voltage	输入电压 Input voltage	额定电流 Rated current	重量(g) Weight (g)	尺寸(mm) Dimension (mm)	输出端子 Output terminal
SD-30V60W-8P	60W	DC24V/DC30V	AC 110V-AC 260V	2A	326	168x70x38	8PIN
SD-30V200W-3P	200W	DC30V		3.5A	1180	235x105x65	3PIN

标准配件 Standard accessories

型号 Model	SD-CA200AT SD-CA300AT SD-CA400AT	SD-CA450AT SD-CA450FAT SD-CA500AT	SD-CA500FAT SD-CA550AT SD-CA550FAT	SD-CA600AT SD-CA600FAT SD-CA620AT	SD-CA630AT SD-CA700AT	SD-CA620FAT SD-CA730AT
电源适配器 Power adapter	SD-30V60W-8P	SD-30V60W-8P	SD-30V60W-8P	SD-30V60W-8P	SD-30V120W-3P	SD-30V120W-3P
连接线 Cable	SD-8P	SD-8P	SD-8P	SD-8P	SD-3P	SD-3P
电源线 Power cord	国标品字尾 National standard three square pins tail	国标品字尾 National standard three square pins tail	国标品字尾 National standard three square pins tail	国标品字尾 National standard three square pins tail	国标品字尾 National standard three square pins tail	国标品字尾 National standard three square pins tail
起子头 Screwdriver bits	∅ 4x40x∅2.5x20x1 # ∅ 4x40x∅2.5x20x0 #	∅ 5x60x1 # ∅ 5x60x2 #	SSH1/4x65x1 # SSH1/4x65x2 #	SSH1/4x65x1 # SSH1/4x65x2 #	SSH1/4x65x1 # SSH1/4x65x2 #	SSH1/4x65x1 # SSH1/4x65x2 #

注:每种配件出厂标配数量为1个

Note:Factory provides only one piece as the standard quantity for each kind of accessory